

## [April-2018-New100% Exam Pass-300-210 Dumps PDF and VCE Free from Braindump2go[187-197]

2018 April New Cisco 300-210 Real Exam Dumps with PDF and VCE Just Updated Today! Following are some new 300-210 Real Exam Questions:1.|2018 Latest 300-210 Exam Dumps (PDF & VCE) 365Q

Download:<https://www.braindump2go.com/300-210.html>2.|2018 Latest 300-210 Exam Questions & Answers

Download:<https://drive.google.com/drive/folders/0B75b5xYLjSSNUm03a0t2b1YySEU?usp=sharing>  
QUESTION 187 Which feature of the Cisco Hybrid Email Security services enables you to create multiple email senders on a single Cisco ESA?A. Virtual GatewayB. Sender GroupsC. Mail Flow Policy ConnectorD. Virtual Routing and ForwardingE. Email Marketing Connector  
**Answer: A**  
QUESTION 188 Which option is a benefit of Cisco Email Security virtual appliance over the Cisco ESA appliance?A. reduced space and power requirementsB. outbound message protectionC. automated administrationD. global threat intelligence updates from Talos  
**Answer: A**  
QUESTION 189 Which option is a benefit of Cisco hybrid email security?A. on-premises control of outbound dataB. advanced malware protectionC. email encryptionD. message tracking  
**Answer: A**  
QUESTION 190 Which technology is used to improve business-critical application performance?A. Application Visibility and ControlB. Intrusion Prevention ServicesC. Advanced Malware ProtectionD. TrustSec  
**Answer: A**  
QUESTION 191 Which option is a benefit of deploying Cisco Application Visibility and Control?A. It ensures bandwidth availability and performance of mission-critical applications in a data- and media-rich environment.B. It performs deep packet inspection of mission-critical applications in a data- and media-rich environment.C. It encrypts mission-critical applications in a data- and media-rich environment.D. It securely tunnels mission-critical applications in a data- and media-rich environment.  
**Answer: A**  
QUESTION 192 Which solution must a customer deploy to prioritize traffic to a cloud-based contact management application while still allowing employees access to the Internet for business and personal use?A. Cisco Application Visibility and ControlB. Cisco Intrusion Prevention ServicesC. Cisco NetFlowD. policy-based routing  
**Answer: A**  
QUESTION 193 Which three categories of the seven major risk management categories are covered in the Cyber Risk Reports? (Choose three.)A. vulnerabilityB. risk ratingC. legalD. confidence levelE. geopoliticalF. global reputation  
**Answer: ACE**  
QUESTION 194 Which option describes a customer benefit of the Cisco Security IntelliShield Alert Manager?A. It provides access to threat and vulnerability information for Cisco related products only.B. It consolidates vulnerability information from an internal Cisco source, which allows security personnel to focus on remediation and proactive protection versus research.C. It provides effective and timely security intelligence via early warnings about new threats and technology vulnerabilities.D. It enhances the efficiency of security staff with accurate, noncustomizable threat intelligence, critical remediation information, and easy-to-use workflow tools.  
**Answer: C**  
QUESTION 195 Which two options are known limitations in deploying an IPS sensor in promiscuous mode versus inline mode? (Choose two).A. It is less effective in stopping email viruses and automated attackers such as worms.B. It requires less of an operational response because the attacks are blocked automatically without operational team support.C. Sensors in this deployment cannot stop the trigger packet and are not guaranteed to stop a connection.D. A sensor failure affects network functionality.E. It does not see the same traffic.  
**Answer: AC**  
QUESTION 196 Which option describes how the native VLAN is set up on an IPS sensor when VLAN groups are used in an inline deployment of the sensor?A. The sensor looks at the native VLAN setup on the switch to determine the correct native VLAN to use.B. The sensor does not care about VLANs.C. A default VLAN variable must be associated with each physical interface on the sensor.D. There is no way to set this, so you need to tag all traffic.E. ISL links are only supported.  
**Answer: C**  
QUESTION 197 Using the Cisco WSA GUI, where should an operator navigate to determine the running software image on the Cisco WSA?A. Systems Administration > System UpgradeB. Systems Administration > Feature KeysC. Systems Administration > GeneralD. Admin > System Info  
**Answer: A**

!!!RECOMMEND!!!1.|2018 Latest 300-210 Exam Dumps (PDF & VCE) 365Q

Download:<https://www.braindump2go.com/300-210.html>2.|2018 Latest 300-210 Study Guide Video: YouTube Video:

[YouTube.com/watch?v=bJZ9vq-b\\_A](https://www.youtube.com/watch?v=bJZ9vq-b_A)